

# UHP Swivel Fitting

Rotation under pressure



The new Parker Polyflex swivel fitting ensures flexibility of the hose assembly, even during operation.

## Product Highlights:

- Easy installation after assembly
- No clamping ring and clamping screw needed
- Flexibility under pressure is given through buffering rotating swivel fitting
- No torsion on the hose while in operation
- Standard connection, interchangeable with a standard adaptor
- Available for -03 (DN 5) and -05 (DN 8) hose types
- Can be used on all 6 and 8 layer hose types that use the 2X fitting series
- All fittings have been qualified for a working pressure up to 4000 bar (58,000 psi)



## Applications:

- General industrial cleaning applications on construction sites and ship docks
- In all UHP applications where rotation is beneficial

## Features:

- Hose remains free of torsion during movements in the application
- Flexibility of the hose when set under pressure

## Benefits:

- Less wear and tear on the assembly, longer lifetime
- Reduced operator fatigue
- Hose can be moved without twisting and kinking it

### Available fitting types:

Nominal Size			
DN	size	DN	size
5	-03	8	-5
3/4-16 UNF, 1 1/8-12 UNF, M16x1,5, M20x1,5, M26x1,5 and M30x2		1 1/8-12 UNF, M26x1,5 and M30x2	